


CMC-G

Male Connector Fittings

Hy-Lok



CMC-G Male Connector Fittings



Connects Metric Tube to Female ISO Parallel thread

PartNo.	Tube OD	T* ISO Thread Size	d+ Min	Width across flat (in.)		A	B	L	L'	L	κ
				h	H						
CMC2M-2G	2	1/8	1.7	14	12	12.9	15.3	24.3	8.0	30.9	13.8
CMC3M-2G	3	1/8	2.3	14	12	12.9	15.3	24.3	8.0	30.9	13.8
CMC3M-4G	3	1/4	2.3	19	12	12.9	15.3	29.5	12.0	36.1	18.0
CMC4M-2G	4	1/8	2.4	14	12	13.7	16.1	25.0	8.0	31.6	13.8
CMC6M-2G	6	1/8	4.0	14	14	15.3	17.7	25.8	8.0	33.2	13.8
CMC6M-4G	6	1/4	4.8	19	14	15.3	17.7	31.0	12.0	38.4	18.0
CMC6M-6G	6	3/8	4.8	22	14	15.3	17.7	32.3	12.0	39.7	21.8
CMC6M-8G	6	1/2	4.8	27	14	15.3	17.7	35.8	14.0	43.2	26.0
CMC8M-2G	8	1/8	4.0	14	16	16.2	18.6	26.6	8.0	34.1	13.8
CMC8M-4G	8	1/4	5.0	19	16	16.2	18.6	31.8	12.0	39.3	13.8
CMC8M-6G	8	3/8	6.3	22	16	16.2	18.6	33.1	12.0	40.6	21.8
CMC8M-8G	8	1/2	6.3	27	16	16.2	18.6	36.7	14.0	44.3	26.0
CMC10M-4G	10	1/4	5.0	19	19	17.2	19.5	32.6	12.0	40.2	18.0
CMC10M-6G	10	3/8	8.0	22	19	17.2	19.5	33.8	12.0	41.4	21.8
CMC10M-8G	10	1/2	8.0	27	19	17.2	19.5	37.4	14.0	45.0	26.0
CMC12M-4G	12	1/4	5.0	13/16 in.	22	22.8	22.0	33.3	12.0	43.4	18.0
CMC12M-6G	12	3/8	8.0	22	22	22.8	22.0	33.8	12.0	43.9	21.8
CMC12M-8G	12	1/2	9.5	27	22	22.8	22.0	37.4	14.0	47.5	26.0
CMC12M-12G	12	3/4	9.5	35	22	22.8	22.0	43.0	16.0	53.1	32.0
CMC16M-6G	16	3/8	8.0	24	25	24.4	22.0	34.6	12.0	44.7	21.8
CMC16M-8G	16	1/2	12.0	27	25	24.4	22.0	37.4	14.0	47.5	26.0
CMC18M-8G	18	1/2	12.0	27	30	24.4	22.0	38.7	14.0	48.8	26.0
CMC18M-12G	18	3/4	15.0	35	30	24.4	22.0	43.0	16.0	53.1	32.0
CMC20M-8G	20	1/2	12.0	30	32	26.0	22.0	40.4	14.0	50.5	26.0
CMC20M-12G	20	3/4	15.7	35	32	26.0	22.0	43.0	16.0	53.1	32.0
CMC22M-12G	22	3/4	15.7	35	32	26.0	22.0	43.0	16.0	53.1	32.0
CMC22M-16G	22	1	18.3	41	32	26.0	22.0	44.9	18.0	55.0	39.0
CMC25M-12G	25	3/4	16.0	35	38	31.3	26.5	45.5	16.0	57.8	32.0
CMC25M-16G	25	1	20.0	41	38	31.3	26.5	47.5	18.0	59.8	39.0
CMC28M-16G	28	1	20.0	41	46	36.6	36.6	49.0	18.0	69.8	39.0
CMC28M-20G	28	1-1/4	23.0	50	46	36.6	36.6	53.3	20.0	74.1	49.0
CMC32M-20G	32	1-1/4	25.0	50	50	42.0	41.6	56.1	20.0	79.1	49.0
CMC38M-24G	38	1-1/2	32.0	55	60	49.4	47.9	63.1	22.0	90.7	54.7

All dimensions are in millimeters unless otherwise specified. Dimensions are for reference only, subject to change.

For leak tight installation, see ISO Parallel and Tapered Pipe Thread on page 7. The d dimension is the minimum nominal opening. These fittings may have a larger opening at the pipe/straight thread end.

