

CI Spare Parts


Hy-Lok



Tube Insert for Nylon or Soft Plastic Tubing

CI**Fractional**

Part No.	Tube OD D		Tube ID D ₁		Bore ID d	
	in.	mm	in.	mm	in.	mm
CI 3 - 2	3/16	4.76	1/8	3.20	0.07	1.7
CI 4 - 2	1/4	6.35	1/8	3.20	0.07	1.7
CI 4 - 4.3M	1/4	6.35	0.17	4.30	0.12	3.1
CI 4 - 3	1/4	6.35	3/16	4.76	0.14	3.5
CI 5 - 2	5/16	7.94	1/8	3.20	0.07	1.7
CI 5 - 3	5/16	7.94	3/16	4.76	0.14	3.5
CI 5 - 4	5/16	7.94	1/4	6.35	0.19	4.8
CI 6 - 3	3/8	9.52	3/16	4.76	0.14	3.5
CI 6 - 4	3/8	9.52	1/4	6.35	0.19	4.8
CI 8 - 4	1/2	12.70	1/4	6.35	0.19	4.8
CI 8 - 6	1/2	12.70	3/8	9.52	0.31	7.8
CI10 - 6	5/8	15.80	3/8	9.52	0.31	7.8
CI10 - 8	5/8	15.80	1/2	12.70	0.44	11.0
CI12 - 8	3/4	19.00	1/2	12.70	0.44	11.0
CI12 - 10	3/4	19.00	5/8	15.87	0.56	14.2
CI16 - 12	1	25.40	3/4	19.05	0.69	17.5

**Metric**

Part No.	Tube OD D	Tube ID D ₁	Bore ID d
CI 6M - 4M	6	4	2.4
CI 8M - 6M	8	6	4.8
CI 10M - 8M	10	8	6.4
CI 12M - 8M	12	8	6.4
CI 12M - 10M	12	10	8.3

Hy-Lok Tube Inserts are used to secure the nylon or other soft plastic tubing to Hy-Lok tube fittings.

To choose the proper Hy-Lok Tube insert, check if O.D. and I.D. of the tubing are the same as dimension D and D₁ of tube inserts, respectively.

All dimensions are in millimeters unless otherwise specified.
Dimensions are for reference only, subject to change.